

# Cascade Server System Tags

August 2010

Tiffany May | Web Developer | Beacon Technologies, Inc. | <http://www.beacontechologies.com> | [tmay@beacontechologies.com](mailto:tmay@beacontechologies.com)

## CONTENT REGION TAGS

```
<system-region name="DEFAULT"/>
```

## METADATA TAGS

```
<system-page-name/>
<system-page-title/>
<system-page-summary/>
<system-page-author/>
<system-page-teaser/>
<system-page-keywords/>
<system-page-description/>
<system-page-display-name/>
<system-page-start-date/>
<system-page-end-date/>
<system-page-meta-date/>
```

*\*these output the full meta element\**

```
<system-page-meta-keywords/>
<system-page-meta-description/>
```

## SYSTEM PSEUDO TAGS

```
[cascade:cdata] [/cascade:cdata]
[system-view:internal] [/system-view:internal]
[system-view:external] [/system-view:external]
[system-asset] [/system-asset]
```

## LINKING

*\*Same Site Links\**

```
/path/to/asset
```

*\*Cross-Site Links\**

```
site://<sitename>/path/to/asset/in/site
```

*\*Asset Local Links\**

```
[system-asset:local]/path/to/asset[/system-asset:local]
```

*\*Link to specific output\**

```
[system-asset:configuration=config] [/system-asset]
```

*\*Link to different output of the current page\**

```
<a system-page-output="outputformat">link </a>
```

## CODE SECTIONS

*\*Passthrough Code Section\**

```
<!--#START-CODE... code here...#END-CODE-->
```

*\*Root Code Section - Place code at the very beginning of a document (before doctype)\**

```
<!--#START-ROOT-CODE ... put any code here... #END-ROOT-CODE-->
```

*\*XSLT for PHP Processing Instruction (not exclusive to Cascade Server)\**

```
<xsl:processing-instruction name="php"></xsl:processing-instruction>
```